

**Title: EU ATEX DIRECTIVE 94/9/EC - DECLARATION OF CONFORMITY - Non Electrical**

The non-electrical rotary actuator range of products manufactured by Kinetrol, as listed below, conform to the requirements of the ATEX Directive 94/9/EC.

Equipment Group: II (Non-mining). Explosive Gas and Dust Atmospheres (GD). Gases Group: IIB or IIC.

Quality Assurance Notification No. SIRA 02 ATEX M166.

Actuators & Spring Units - ATEX Category 1 - Certificate No. BASEEFA 03 ATEX 0443X.


Other Category 2 & 3 approvals covered by Kinetrol internal documentation KTR118, KTR120, KTR121 & KTR124.

Category 2 Actuator Dossier Receipt: Baseefa04ATEX 0146DR/RN2 (KTR118).

Product Code	Category of Approval for each Actuator Size														
	01	02	03	05	07	08	09	10	12	14	15	16	18	20	30
**0-100/**4-100	1	1	1	1	1	2	2	2	2	2	2	2	2	2	2
**5-100/**B-100	-	-	1	1	1	2	2	2	2	2	2	-	-	-	-
**9-100/**7-100	1	1	1	1	1	2	2	2	2	2	2	2	2	2	2
**6-100/**C-100	-	-	1	1	1	2	2	2	2	2	2	-	-	-	-
**1-100/**3-100	-	-	1	1	1	-	2	2	2	2	2	2	-	-	-
**2-100/**A-100	-	-	1	1	1	-	2	2	2	2	2	2	-	-	-
***F100	-	-	1	1	1	2	2	-	-	-	-	-	-	-	-
***-020	1	1	1	1	1	2	2	2	2	2	2	2	2	2	2
***F020	-	-	1	1	1	2	2	2	2	2	2	2	2	2	-
***S020	-	-	-	1	1	-	2	-	-	-	-	-	-	-	-
***-1001	-	2	2	2	2	-	2	2	2	2	2	2	-	-	-
***-0205	-	-	2	2	2	-	2	-	2	2	2	2	2	-	-
***-0206	-	-	2	2	2	-	2	-	2	-	-	-	-	-	-
024-020-1016	-	2	-	-	-	-	-	-	-	-	-	-	-	-	-
***-020-1016/7	-	-	2	2	2	-	-	-	-	-	-	-	-	-	-
***F020-1016/7	-	-	2	2	2	-	-	-	-	-	-	-	-	-	-
***S020-1016/7	-	-	-	2	2	-	-	-	-	-	-	-	-	-	-
054-020-1012	-	-	-	2	-	-	-	-	-	-	-	-	-	-	-
0** K/BOX	-	-	-	2	2	-	2	2	2	2	-	-	-	-	-
G3 D/BOX	-	-	-	-	-	-	-	-	-	2	2	2	2	2	-
**_**L	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
***_***-2100	-	-	-	1	1	-	2	2	2	2	2	2	2	2	2
***_***-2104	1	1	1	1	1	2	2	2	2	2	2	2	2	2	2
***-100-2118	2	2	2	2	2	-	-	-	-	-	-	-	-	-	-
(***-900-4660/1/2)	-	-	-	-	-	-	-	-	1	1	-	-	-	-	-
***_***-2200	-	-	-	-	-	-	-	-	1	1	-	-	-	-	-
***_***-2201	-	-	-	-	-	-	-	-	1	1	-	-	-	-	-
***_**2	-	2	2	2	2	2	2	2	2	2	-	-	-	-	-
***_**2U0000*0	-	-	2	2	2	2	2	2	2	2	2	2	2	2	2

- \*\*\* Denotes actuator size & thread option. Refer to Kinetrol catalogue for full size range details.
- 2118 also covers 020-900-4660/1/2 stainless steel case.
  - 'L' option lowers minimum ambient temperature to -40°C (Category 2 only).
  - All spring options can be 020, 030, 080 or 090 depending on direction of wind of spring or mounting flange option.
  - "Low pressure" spring options are approved to Category 2 – refer to catalogue KF84.
  - Kinetrol valve mounting brackets and couplings are included to Category 1.
  - Restricted angular stroke actuators are approved to Category 2 as referred to in TD15.
  - Kinetrol AP positioner is approved as a mechanical device to Category 1 – refer to Kinetrol for separate certificate for this approval.
  - EL positioner options, limit switch options and AP electrical options are also available with ATEX approval to Category 1 or 2 – refer to Kinetrol for further information.

Complies with Health & Safety requirements by compliance with: EN13463-1:2009, EN13463-5:2011.

  
R.C.Chapman, Engineering Manager

Issue	Signed	Date	<b>KINETROL</b>	Trading Estate, Farnham, Surrey, GU9 9NU, England	Doc.No. TD125-1
Z	T.L.	16/02/16			Page 1 of 1